

**20' Half Height
-Removable Side Door
Offshore Container
20'x8'x4'
DNV/ISO Corner Castings**



DNV Certification Note 2.7-1:
Offshore Containers
EN 12079: Offshore Containers
ISO 1161 Corner Fittings
The Convention for Safety Containers CSC
Classification Society: Bureau Veritas
DNV/ISO Corner Casting
Allows for any intermodal
means of transportation
Handling Options: Forklift, Crane or Top Lift
Truck, Rail, Ocean Transport
Reduces Dray Costs



Options

DNV Certified IWRC
Wire Rope Lifting Sling
Equipped with Safety Pin Bow Shackles
And
Flemish Steel Splice Terminations

Dimensions

20' (L) x 8' (W) x 4'3" (H)

| External | Internal | Capacity |
|--------------------|--------------------|-----------|
| 6058 mm (19'10.4") | 5738 mm (18'9.96") | 11.5 Cu.m |
| 2438 mm (8'0") | 2116 mm (6'11.3") | |
| 1295 mm (4'3") | 945 mm (3'1.2") | |



Ratings

| | |
|----------------------|-----------|
| Max Gross | 20,000 kg |
| Payload | 15,650 kg |
| Tare (+/- 2%) | 4,350 kg |

FIRST CHOICE FOR SPECIALIST DNV CABINS,
SPECIALIST MODULES, CONTAINERS AND BASKETS